



The AC16 articulating carrier is designed and built for mill yard duties with powerful tractive effort and durable construction throughout. Tigercat's WideRange™ drive provides quick travel speeds without the need to shift gears.

BENEFITS AND ADVANTAGES:

Durable construction with Tigercat fabricated frames and high quality components

Heavy duty forestry axles

Simple, robust and efficient WideRange drive

Four-wheel drive with powerful tractive effort for towing applications and tough terrain

Quick travel speeds

Loader and carrier can be separated

Optional bar or circle saw slasher hydraulics

Optional bunk and stakes

Available with the 234 and 250 series loaders



Tigercat 234 and 250 series loaders are an excellent choice for the mill yard with efficient load sensing hydraulics, a unique energy recovery swing system, strength-to-weight optimized boom components and excellent service access.

SPECIFICATIONS

DIMENSIONS

LENGTH carrier only	8 155 mm (321 in)
With 234B less boom	8 660 mm (341 in)
With 250D (mill yard) less boom	8 865 mm (349 in)
HEIGHT with 234B	4 800 mm (189 in)
HEIGHT with 250D	4 800 mm (189 in)
WIDTH	3 100 mm (122 in)
WHEELBASE	5 385 mm (212 in)
GROUND CLEARANCE	460 mm (18 in)
ARTICULATION	+/-37°
TURN RADIUS inside	7 m (23 ft)
WEIGHT carrier only	7 260 kg (16,000 lb)

POWER TRAIN

TRANSMISSION	Tigercat WideRange™ drive Variable speed hydraulic (2) Piston motors, infinitely variable Front oscillating +/-5°, 37R series Rear fixed, 37R series Front
AXLES	
DIFFERENTIAL LOCKS	
TRACTIVE EFFORT	
234B	95 kN (21,500 lbf)
250D	102 kN (23,000 lbf)
TOP SPEED	13 km/h (8 mph)

BRAKES

DYNAMIC BRAKING	Hydraulic
SECONDARY BRAKES	Enclosed, oil cooled
PARK BRAKE	Caliper; Spring applied/hydraulic release

TIRES

STANDARD	23.5x25
----------	---------

OPTIONAL EQUIPMENT

Circle saw slasher hydraulics
Bar saw slasher hydraulics
Butt plate
Log bunks, front frame
Pintle hitch

TIGERCAT RESERVES THE RIGHT TO AMEND THESE SPECIFICATIONS AT ANY TIME WITHOUT NOTICE

widerANGE™ Tigercat's highly efficient WideRange drive system provides powerful tractive effort and quick working travel speed without the need to change gears.

With powerful tractive effort and optional hydraulic packages for auxiliary equipment, the AC16 articulating carrier increases versatility and expands the range of duties the loader can accomplish in mill yard applications.



Optional bunk and stakes for additional carrying capacity. Combined with a trailer, the AC16 has the potential to quickly move large volumes of timber around the yard.



Optional bar and circle saw slasher hydraulic packages available for merchandising in the mill yard.

© 2001 - 2015 Tigercat International Inc. All Rights Reserved. TIGERCAT, WIDERANGE, TURNAROUND, ER, EHS, and TEC, their respective logos, TOUGH RELIABLE PRODUCTIVE, TIGERCAT TV, "Tigercat Orange" and BETWEEN THE BRANCHES, as well as corporate and product identity, are trademarks of Tigercat International Inc., and may not be used without permission. TIGERCAT, TURNAROUND, and ER, and their respective logos are registered trademarks of Tigercat International Inc.

54 Morton Ave. East
Branford, Ontario
Canada, N3R 7J7
Mail: Box 637 N3T 5P9

E-mail: comments@tigercat.com
Internet: www.tigercat.com
Tel: (519) 753-2000
Fax: (519) 753-8272

(7055) 3 0515•Tig

Tigercat®