

LX830E

FELLER BUNCHER



CLOSED LOOP DRIVE AND NEAR ZERO TAIL SWING.

Tigercat®
Tough • Reliable • Productive

THE LX830E IS POWERFUL, EFFICIENT, AND VERSATILE FOR SELECTIVE AND FINAL FELLING IN STEEP TERRAIN CONDITIONS. THE CLOSED LOOP TRACK DRIVE SYSTEM PROVIDES HIGHEST PERFORMANCE AND EFFICIENCY WHEN OPERATING ON SLOPES.

KEY BENEFITS

- ▶ Near zero tail swing for effective selective felling performance and ample chain clearance in winch assist applications
- ▶ ER boom technology® improves fuel efficiency, reduces operator fatigue and increases productivity
- ▶ Extreme duty leveling undercarriage for excellent stability on steep slopes
- ▶ Power operated roof enclosure completely exposes the engine and major components while serving as a safe and convenient work platform

EXCELLENT OPERATOR COMFORT

- ▶ Full shift comfort. Highly adjustable parallel action air ride seat with integrated heating and cooling. Comfortable cab interior with clear sightlines. Ergonomic positioning of controls and display screens.



TIGHT TUCK ER BOOM

- ▶ The ER boom system is efficient and easy to operate. Quick cycles lead to high productivity in smaller diameter timber and thinning applications. The tight tuck preserves the residual stand. Excellent performance in larger timber with ample stability to handle the high capacity 5702-26 felling saw.



OPEN ACCESS

- ▶ The clamshell style engine roof completely exposes the top and both sides of the engine, and most hydraulic components. When open, the enclosure roof serves as a spacious service platform to work comfortably and safely.




DESIGNED FOR STEEP SLOPES

- ▶ Optimized weight distribution and low centre of mass, along with Tigercat's patented super duty leveling undercarriage, provide excellent stability and performance on steep slopes.



LX830E FELLER BUNCHER

POWER: 257 kW (350 hp)
CUT RADIUS: 8,43 m (27 ft 8 in)
TAIL SWING RADIUS: 2,1 m (6 ft 11 in)



Scan the QR code then click 'SPECS' for a full list of machine specifications for the LX830E feller buncher.

Download the Tigercat App or visit [tigercat.com](https://www.tigercat.com) to access the most current machine specifications for all Tigercat and TCi machine models.

EMAIL	comments@tigercat.com
PHONE	519.753.2000
WEBSITE	www.tigercat.com
ADDRESS	54 Morton Ave. East, Brantford, Ontario Canada, N3R 7J7
MAIL	Box 637 N3T 5P9

© 2001 - 2026 Tigercat International Inc. All Rights Reserved. TIGERCAT, WIDERANGE, TURNAROUND, ER, EHS, LOW-WIDE, TEC, REMOTELOG, LOGON, TCI, and their respective logos, TOUGH RELIABLE PRODUCTIVE, TIGERCAT TV, "Tigercat Orange" and BETWEEN THE BRANCHES, as well as corporate and product identity, are trademarks of Tigercat International Inc., and may not be used without permission. TIGERCAT, TCI, TURNAROUND, WIDERANGE, EHS, LOW-WIDE, ER and REMOTELOG, and their respective logos are registered trademarks of Tigercat International Inc.