

234C LOADER



HIGH PERFORMANCE AND EFFICIENCY FOR
MERCHANDIZING AND LOADING.

Tigercat®
Tough • Reliable • Productive

THE 234C CAN BE EQUIPPED WITH A PULL-THROUGH DELIMBER, BAR SAW SLASHER, CIRCLE SAW SLASHER OR GRAPPLE SAW FOR MAXIMUM FLEXIBILITY.

EFFICIENT HYDRAULICS WITH SWING PRIORITY AND ENERGY RECOVERY DELIVER SIMULTANEOUS POWER TO ALL MACHINE FUNCTIONS FOR HIGH PERFORMANCE, RESPONSE AND FUEL EFFICIENCY.

KEY BENEFITS

- ▶ Efficient load sensing hydraulic system. High performance, low fuel consumption
- ▶ Energy recovery swing system. Closed loop system recovers energy as swing decelerates
- ▶ Dedicated swing pump. Quick swing cycles, enhanced pull-through delimbing performance
- ▶ Automatic engine idle down. Reduced fuel consumption in variable wood flow situations
- ▶ Strength-to-weight optimized boom. Designed for heavy lifting and pull-through delimbing
- ▶ Quiet, comfortable, climate controlled operating environment



OPERATING ENVIRONMENT

- ▶ The new operator's cab has 16% larger volume with increased width and more leg room. Improved A/C and heater controls allow the operator to set the desired temperature for a more comfortable working environment. A climate controlled cupholder keeps drinks hot or cold for longer. Dedicated storage areas include space for a full size Tigercat insulated lunchbox behind the seat.



BUILT FOR THE JOB

- ▶ The 234C hydraulic system uses a larger hydraulic pump, and a new boom valve for improved flow sharing. The new boom design has thicker steel and improved geometry to handle the increased lift capacity and swing torque. Cushioned boom cylinders provide smooth control to take advantage of the faster speeds that the hydraulic system delivers. Through-tip grapple hose routing protects from damage.



SERVICE MADE SIMPLE

- ▶ The large panel on the cab platform provides unmatched access to engine service points. The removable deck plates on the platform allow for easy access to hydraulic valves and hoses.



234C LOADER

POWER: 125 kW (168 hp)
REACH: 9,75 m (32 ft)
LIFT at 7,6m (25 ft): 6 800 kg (15,000 lb)



Scan the QR code then click 'SPECS' for a full list of machine specifications for the 234C loader.

Download the Tigercat App or visit [tigercat.com](https://www.tigercat.com) to access the most current machine specifications for all Tigercat machine models.

EMAIL	comments@tigercat.com
PHONE	519.753.2000
WEBSITE	www.tigercat.com
ADDRESS	54 Morton Ave. East, Brantford, Ontario Canada, N3R 7J7
MAIL	Box 637 N3T 5P9

© 2001 - 2025 Tigercat International Inc. All Rights Reserved. TIGERCAT, WIDERANGE, TURNAROUND, ER, EHS, LOW-WIDE, TEC, REMOTELOG, LOGON, TCI, and their respective logos, TOUGH RELIABLE PRODUCTIVE, TIGERCAT TV, "Tigercat Orange" and BETWEEN THE BRANCHES, as well as corporate and product identity, are trademarks of Tigercat International Inc., and may not be used without permission. TIGERCAT, TCI, TURNAROUND, WIDERANGE, EHS, LOW-WIDE, ER and REMOTELOG, and their respective logos are registered trademarks of Tigercat International Inc.