250E LOADER

SUITED TO HEAVY TIMBER AND TOUGH DUTY CYCLE DELIMBING AND MERCHANDISING.

Tigercat®
Tough • Reliable • Productive

THE 250E IS SUITED TO DELIMBING, MERCHANDISING AND LOADING HEAVY, TREE-LENGTH TIMBER. THE 250E CAN BE EQUIPPED WITH A PULL-THROUGH DELIMBER, BAR SAW SLASHER, CIRCLE SAW SLASHER OR GRAPPLE SAW FOR MAXIMUM FLEXIBILITY.

EFFICIENT HYDRAULICS WITH SWING PRIORITY AND ENERGY RECOVERY DELIVER SIMULTANEOUS POWER TO ALL MACHINE FUNCTIONS FOR HIGH PERFORMANCE, RESPONSE AND FUEL ECONOMY.

KEY BENEFITS

- Efficient load sensing hydraulic system. High performance, low fuel consumption
- Energy recovery swing system. Closed loop system recovers energy as swing decelerates
- Dedicated swing pump. Quick swing cycles, enhanced pull-through delimbing performance
- Automatic engine idle down. Reduced fuel consumption in variable wood flow situations
- Strength-to-weight optimized boom. Designed for heavy lifting and pull-through delimbing
- Quiet, climate controlled operating environment

OPERATING ENVIRONMENT

- The new operator's cab has 16% larger volume with increased width and more legroom. Set it and forget it. Improved A/C and heater controls allow the operator to set the desired temperature for a more comfortable working environment. Climate controlled cupholders keep drinks hot or cold for longer. Dedicated storage areas include space for a full size Tigercat insulated lunchbox behind the seat.

POWERFUL BOOM SYSTEM

- Strong boom and powerful swing torque. The new 250 series boom design is stronger and better able to handle the stresses of the most demanding pull-through delimbing duty cycles. Cushioned boom cylinders provide smooth control. Through-tip grapple hose routing protects from damage.

GREAT SERVICE ACCESS

- The large panel on the cab platform provides unmatched access to engine service points. The removable deck plates on the platform allow for easy access to hydraulic valves and hoses.

Tigercat®

250E LOADER

POWER:	151 kW (203 hp)
REACH:	9,75 m (32 ft)
LIFT at 7,6m (25 ft):	8 165 kg (18,000 lb)

Scan the QR code then click 'SPECS' for a full list of machine specifications for the 250E loader.

Download the Tigercat App or visit tigercat.com to access the most current machine specifications for all Tigercat and TCi machine models.

EMAIL	comments@tigercat.com
PHONE	519.753.2000
WEBSITE	www.tigercat.com
ADDRESS	54 Morton Ave. East, Brantford, Ontario Canada, N3R 7J7
MAIL	Box 637 N3T 5P9

© 2001 - 2025 Tigercat International Inc. All Rights Reserved. TIGERCAT, WIDERANGE, TURNAROUND, ER, EHS, LOW-WIDE, TEC, REMOTELOG, LOGON, TCI, and their respective logos, TOUGH RELIABLE PRODUCTIVE, TIGERCAT TV, "Tigercat Orange" and BETWEEN THE BRANCHES, as well as corporate and product identity, are trademarks of Tigercat International Inc., and may not be used without permission. TIGERCAT, TCI, TURNAROUND, WIDERANGE, EHS, LOW-WIDE, ER and REMOTELOG, and their respective logos are registered trademarks of Tigercat International Inc.

CV1063
250E 1.0 0325