

LX825

FELLER BUNCHER



CONVERTIBLE FELLER BUNCHER AND MULCHER CARRIER.

Tigercat®
Tough • Reliable • Productive

THE LX825 IS A COMPACT, LIGHT-WEIGHT CARRIER DESIGNED FOR PRECISION THINNING AND MASTICATION WITH MINIMAL SITE IMPACT. IT IS WELL SUITED TO FUEL REDUCTION AND FIRE MITIGATION APPLICATIONS IN STEEP AND ROCKY TERRAIN.

KEY BENEFITS

- ▶ Optional convertible mulcher/feller buncher hydraulic system. Flexibility to easily switch between a disc saw saw, bar saw, or mulching head
- ▶ Near zero tail swing for effective selective felling performance and ample chain clearance in winch assist applications
- ▶ ER boom technology® improves fuel efficiency, reduces operator fatigue and increases productivity
- ▶ Leveling undercarriage with smaller footprint for lower weight and increased agility
- ▶ Power operated roof enclosure completely exposes the engine and major components while serving as a safe and convenient work platform

EXCELLENT OPERATOR COMFORT

- ▶ Full shift comfort. Highly adjustable parallel action air ride seat with integrated heating and cooling. Comfortable cab interior with clear sightlines. Ergonomic positioning of controls and display screens. Convenient HVAC controls allow the operator to adjust fan speed and temperature using the switches on the control panel, or the machine control system touchscreen.



TIGHT TUCKER BOOM

- ▶ The ER boom system contributes to excellent fuel economy and reduced operator fatigue. It is perfectly matched to the lighter weight LX825 carrier and optimized for quick cycles. Tight tuck geometry increases the boom envelope and helps to preserve the residual stand.



OPEN ACCESS

- ▶ The clamshell style engine roof completely exposes the top and both sides of the engine, valves, cooling system, and daily service points. When open, the enclosure roof serves as a spacious service platform to work comfortably and safely.
- ▶ A large, spring-assisted pump cover provides easy access to the hydraulic pump area.



DESIGNED FOR STEEP SLOPES

- ▶ Optimized weight distribution and low centre of mass, along with a lighter weight F8 leveling undercarriage, provide excellent stability, speed, responsiveness and performance on steep slopes.
- ▶ Closed loop drive system provides ample tractive effort for tough terrain, while maintaining excellent multi-functioning capability, quick travel speeds and high efficiency.



LX825 FELLER BUNCHER

POWER standard: 257 kW (350 hp)

POWER convertible system: 272 kW (370 hp)

CUT RADIUS: 8,43 m (27 ft 8 in)

TAIL SWING RADIUS: 2,1 m (6 ft 11 in)



Scan the QR code then click 'SPECS' for a full list of machine specifications for the LX825 feller buncher.

Download the Tigercat-TCi App or visit tigercat.com to access the most current machine specifications for all Tigercat and TCi machine models.

EMAIL	comments@tigercat.com
PHONE	519.753.2000
WEBSITE	www.tigercat.com
ADDRESS	54 Morton Ave. East, Brantford, Ontario Canada, N3R 7J7
MAIL	Box 637 N3T 5P9

© 2001 - 2026 Tigercat International Inc. All Rights Reserved. TIGERCAT, WIDERANGE, TURNAROUND, ER, EHS, LOW-WIDE, TEC, REMOTELOG, LOGON, TCI, and their respective logos, TOUGH RELIABLE PRODUCTIVE, TIGERCAT TV, "Tigercat Orange" and BETWEEN THE BRANCHES, as well as corporate and product identity, are trademarks of Tigercat International Inc., and may not be used without permission. TIGERCAT, TCI, TURNAROUND, WIDERANGE, EHS, LOW-WIDE, ER and REMOTELOG, and their respective logos are registered trademarks of Tigercat International Inc.